

CENTAURE™ Wheels Material Handling Wheels

6" to 16" diameter –
2¼" to 3" Hub Lengths

385 lbs to 1,100 lbs Capacity

Solid rubber tires mounted on steel zinc-coated center
Bolted for easy maintenance



Product numbers listed in highlighted boxes				
BORE LENGTH & TYPE	2-1/4" CENTERED	2-1/4" CENTERED	3" CENTERED	
BEARING TYPES	Ball Bearing	Roller Bearing	Roller Bearing	Centaure Load Rating
BORE SIZES	1/2", 5/8", 3/4"	5/8", 3/4" & 1"	3/4" & 1"	lbs
WHEELS O.D.				
6" x 1-3/4" (Tread = 1.25")	746.163.xx0y	745.163.xx06		385
7" x 2" (Tread = 1.25")	746.184.xx0y	745.184.xx06		390
8" x 2" (Tread = 1.5")	746.207.xx0y	745.207.xx06		440
10" x 2" (Tread = 1.5")	736.251.xx0y	735.251.xx06		450
12" x 2" (Tread = 1.5")	736.303.xx0y	735.303.xx06		550
14" x 2-3/4" (Tread = 1.75")			737.360.xx06	1000
16" x 3" (Tread = 1.75")			737.405.xx06	1100

Conversion code numbers for letters in above grid:

Bore Ø	1/2"	5/8"	3/4"	1"
xx	13	15	19	26

Bearing & Accessories Choice	Ball Bearing	Heavy Duty Ball Bearing	Precision Flanged Ball Bearing	Delrin Bushing	Zirk	Roller Bearing
y	0	HD	SB	3	Z	6