

SNAPLOCK™ Wheels Equipment Wheels

6" to 12" diameter –
2" to 4½" Hub Length

Residential Waste Container Wheels
330 lbs Capacity

Quiet-rolling solid rubber tire mounted on durable impact-resistant poly hub

Spring-loaded mechanism locks on grooved axle

Thru Hole version available for 2" hub length



Product numbers listed in highlighted boxes

BORE LENGTH & TYPE	2" OFFSET	2-5/8" OFFSET	3" OFFSET	3-3/4" OFFSET	4" OFFSET	4-1/2" OFFSET	SnapLock Load Rating lbs
BEARING TYPES	No Bearing	No Bearing	No Bearing	No Bearing	No Bearing	No Bearing	
BORE SIZES	5/8", 3/4" & 7/8"	5/8", 3/4" & 7/8"	5/8", 3/4" & 7/8"	5/8" & 7/8"	3/4" & 7/8"	3/4" & 7/8"	
WHEELS O.D.							
6" x 1-3/4" (Tread = 1.25")		682.163.xx11 682.163.xx12		681.163.xx11			330
8" x 2" (Tread = 1.25")		682.201.xx11 682.201.xx12		681.201.xx11			330
10" x 2" (Tread = 1.5")	688.236.xx11 688.236.xx12		689.236.xx11				330
12" x 2" (Tread = 1.25")	687.294.xx11 687.294.xx12		686.294.xx11				330
10" x 2" (Tread = 2.0")			618.261.1912 (3/4")		619.261.xx12	620.261.2212	330
12" x 2" (Tread = 2.0")			618.308.1912 (3/4")		619.308.xx12	620.308.2212	330
	– Fits all carts, add spacers	– Fits Rehrig carts and others	– Fits Rehrig and Ameri-Kart Carts	– Fits Schaefer, IPL and Otto carts	– Fits Schaefer carts	– Fits IPL and Otto carts	

SKUs are Thru-Hole (TH) plain bore, for mounting on straight axles.

Conversion code numbers for letters in above grids:

Bore Ø	5/8"	3/4"	7/8"
xx	16	19	22

NEW PRODUCT



6" SnapLock

Axle Style

TYPE	1	2
y	SnapLock	Thru-Hole



SNAPLOCK II™ Wheels *New Product!!!* Equipment Wheels

Same Great Features as the SnapLock –
Now In A Lightweight Version!
330 lbs Capacity

MEETS ANSI Z245.30 REQUIREMENTS

Quiet-rolling solid rubber tread on a durable impact-resistant poly center

Spring-loaded pin locks into grooved axle

Available with an economical plastic tread SnapLock

Removable wheel with access to locking mechanism



New Rubber Treaded "Fan" Wheel

NEW SNAP LOCK ALL-PLASTIC WHEELS		NEW PRODUCTS				SnapLock Load Rating lbs
BORE LENGTH & TYPE	2" OFFSET	3" OFFSET	4" OFFSET	4-1/2" OFFSET		
BEARING TYPES	No Bearing	No Bearing	No Bearing	No Bearing		
BORE SIZES	5/8", 3/4" & 7/8"	5/8", 3/4" & 7/8"	3/4" & 7/8"	7/8"		
WHEELS O.D.						
All Plastic	10" x 2" (Tread = 1.75")	794.250.xx1y	793.250.xx11	792.250.xx11	791.250.xx11	330
	12" x 2" (Tread = 1.75")	794.300.xx1y	793.300.xx11	792.300.xx11	791.300.xx11	330
Rubber Tread	10" x 2" (Tread = 1.75")	694.250.xx1y	693.250.xx11	692.250.xx11	691.250.xx11	330
	12" x 2" (Tread = 1.75")	694.300.xx1y	693.300.xx11	692.300.xx11	691.300.xx11	330
		- Fits all carts, add spacers	- Fits Rehrig and Ameri-Kart Carts	- Fits Schaefer carts	- Fits IPL and Otto carts	

Coming Soon!

Conversion code numbers for letters in above grids:			
Bore Ø	5/8"	3/4"	7/8"
xx	15	19	22

Axle Style		
TYPE	1	2
y	SnapLock	Thru-Hole



New All Plastic "Fan" Wheel