

Same Great Features as the SnapLock –
Now In A Lightweight Version!
330 lbs Capacity

MEETS ANSI Z245.30 REQUIREMENTS

Quiet-rolling solid rubber tread on a durable impact-resistant poly center

Spring-loaded pin locks into grooved axle

Available with an economical plastic tread SnapLock

Removable wheel with access to locking mechanism



New Rubber Treaded "Fan" Wheel

NEW SNAP LOCK ALL-PLASTIC WHEELS		NEW PRODUCTS				SnapLock Load Rating lbs
BORE LENGTH & TYPE	2" OFFSET	3" OFFSET	4" OFFSET	4-1/2" OFFSET		
BEARING TYPES	No Bearing	No Bearing	No Bearing	No Bearing		
BORE SIZES	5/8", 3/4" & 7/8"	5/8", 3/4" & 7/8"	3/4" & 7/8"	7/8"		
WHEELS O.D.						
All Plastic	10" x 2" (Tread = 1.75")	794.250.xx1y	793.250.xx11	792.250.xx11	791.250.xx11	330
	12" x 2" (Tread = 1.75")	794.300.xx1y	793.300.xx11	792.300.xx11	791.300.xx11	330
Rubber Tread	10" x 2" (Tread = 1.75")	694.250.xx1y	693.250.xx11	692.250.xx11	691.250.xx11	330
	12" x 2" (Tread = 1.75")	694.300.xx1y	693.300.xx11	692.300.xx11	691.300.xx11	330
		- Fits all carts, add spacers	- Fits Rehrig and Ameri-Kart Carts	- Fits Schaefer carts	- Fits IPL and Otto carts	

} *Coming Soon!*

Conversion code numbers for letters in above grids:

Bore Ø	5/8"	3/4"	7/8"
xx	15	19	22

Axle Style

TYPE	1	2
y	SnapLock	Thru-Hole



New All Plastic "Fan" Wheel